

Ceiling Concealed Split Units		Advance Specifications							
A. Air Handling Unit Model	50Hz	P1AL014P6A		P1AL018P6A		P1AL024P6A		P1AL036P6A	
	60Hz	P1AL014P7A		P1AL018P7A		P1AL024P7A		P1AL036P7A	
Nominal Cooling Capacity (Btu/h/kW)		13,300	3.9	18,000	5.3	24,000	7.0	36,000	10.6
Nominal Airflow (CFM/CMH)		400	680	600	1,020	800	1,360	1,200	2,040
Motor Hp		1/10		1/10		1/10		1/4	
Cabinet Dimensions (in/mm):	Height	10	261	10	261	10	261	13	330
	Width	39	1,000	39	1,000	39	1,000	43	1,100
	Depth	20	501	20	501	20	501	22	555
Operating Weight (lbs/kgs)		70	32	73	33	75	34	103	47
B. Condensing Unit Model	50Hz	P1AC014N6A		P1AC018N6A		P1AC024N6A		P1AC036P6A	
	60Hz	P1AC014N7A		P1AC018N7A		P1AC024N7A		P1AC036P7A	
Motor Hp		1/12		1/5		1/5		1/4	
Electrical Characteristics (V/Ph/Hz)	50Hz	220-240/1/50		220-240/1/50		220-240/1/50		220-240/1/50	
	60Hz	208-230/1/60		208-230/1/60		208-230/1/60		208-230/1/60	
Compressor Type		Rotary		Rotary		Reciprocating		Reciprocating	
Power Input - Accu (kW)		1.38		1.93		2.60		3.76	
Cabinet Dimensions (in/mm):	Height	20	520	25	623	25	623	31	792
	Width	29	745	35	895	35	895	40	1,016
	Depth	9.8	250	13	331	13	331	14	355
Operating Weight (lbs/kgs)		74.8	34	103.4	47	136.4	62	194	88
Gas Line Connection Dia. (in/mm)		1/4	6	3/8	10	3/8	10	1/2	13
Suction Line Connection Dia. (in/mm)		1/2	13	5/8	16	5/8	16	3/4	19